



Velocidad N inalámbrica de 300Mbps

TL-WR840N V6.20

CARACTERÍSTICAS DE HARDWARE

Interface	4 10/100Mbps LAN PORTS 1 10/100Mbps WAN PORT
Botón	WPS/RESET Button
Fuente de Alimentación Externa	9VDC / 0.6A
Estándares Inalámbricos	IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Dimensiones (W X D X H)	7.2 x 5.0 x 1.4in.(182 x 128 x 35 mm)
Antenas	2 Antennas

CARACTERÍSTICAS INALÁMBRICAS

Frecuencia	2.4-2.4835GHz
Tasa de Señal	11n: Up to 300Mbps(dynamic) 11g: Up to 54Mbps(dynamic) 11b: Up to 11Mbps(dynamic)
Sensibilidad de Recepción	270M: -68dBm@10% PER 130M: -68dBm@10% PER 108M: -68dBm@10% PER 54M: -68dBm@10% PER 11M: -85dBm@8% PER 6M: -88dBm@10% PER 1M: -90dBm@8% PER
Potencia de Transmision	CE: <20dBm FCC: <30dBm

CARACTERÍSTICAS INALÁMBRICAS

Funciones Inalámbricas	Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
Seguridad Inalámbrica	64/128-bit WEP, WPA / WPA2, WPA-PSK / WPA2-PSK

CARACTERÍSTICAS DE SOFTWARE

Calidad de servicio	WMM, Bandwidth Control
WAN Type	Dynamic IP/Static IP/PPPoE/ PPTP/L2TP
Administración	Access Control Local Management Remote Management
DHCP	Server, Client, DHCP Client List, Address Reservation
Port Forwarding	Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS	DynDns, Comexe, NO-IP
VPN Pass-Through	PPTP, L2TP, IPSec (ESP Head)
Control de Acceso	Parental Control, Local Management Control, Host List, Access Schedule, Rule Management

CARACTERÍSTICAS DE SOFTWARE

Seguridad de cortafuegos	DoS, SPI Firewall IP Address Filter/MAC Address Filter/Domain Filter IP and MAC Address Binding
Protocolos	Support IPv4 and IPv6
Red de invitados	2.4GHz Guest Network x1
OTROS	
Certificacion	CE, RoHS
Contenido del paquete	Wireless N Router TL-WR840N Power supply unit Ethernet Cable Quick Installation Guide
Requisitos del Sistema	Windows 2000/XP/Vista™, Windows 7, Windows 8, Windows 8.1, Windows 10 or Mac OS or Linux-based operating system
Ambiente	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing